



TIKKURILA


AKVI ISOLATOR

Special primer for wooden surfaces

A water-borne, acrylate-based, special primer Akvi Isolator has been developed to retard knot bleedings and seepage of the resin. This fast-drying paint has been especially optimized for rapid production lines. The product has also good stacking properties.

The new primer is designed for wooden panels, mouldings, doors and other wooden surfaces for interior use.

- Retards knot bleeding
- Slows down discoloring of topcoat caused by resin.
- Best results achieved with a two-layer system
- Fast drying
- Good stacking properties




AKVI ISOLATOR

Special primer for wooden surfaces

DURABLE, WATER-BORNE SOLUTION FOR INTERIOR WOODEN SURFACES

The best wood treatment results can be achieved with a system consisting of Akvi Isolator applied in two layers, and finished with Tikkurila water-borne topcoats Akvi Top DS 25, Akvi Top FD 30 or the water-borne UV-curing paint Luminol 25.

Akvi Isolator can be applied by airless spraying, air-assisted airless spraying or traditional spraying with a thinning of 0-5%.



PRODUCT INFORMATION

Code item: 005 3841 00 70
 Color: white
 Gloss level: matt
 Can size: 20 l

AKVI ISOLATOR PAINT SYSTEM

Treatment	Product	Application method	Spreading amount /wet
Priming	1-2 x Akvi Isolator	airless spraying	150 g/m ²
Finishing	1 x Akvi Top DS 25, Akvi Top FD 30 or Luminol 25	airless spraying	120 g/m ²